



## HFHURZ DLONBFHVRSSHU

### Technical Specifications

<b>MATERIAL:</b>	100% High-density Polyethylene (conforms with ASTM 3350)
<b>COLORS:</b>	Yellow, Black
<b>DIAMETER:</b>	4.5"
<b>LENGTH:</b>	Available in 100' (46" x 46" x 21" – 27lbs) and 250' (62" x 62" x 21" – 67lbs) coils, can be cut to any size
<b>STANDARDS:</b>	FenceCrown meets or exceeds all specifications when run to the following standards: ASTM F405-13, ASTM F 667-12, AASHTO M 252, AASHTO M 294 and NRCS Conservation Practice Standard Code 606.
<b>STIFFNESS:</b>	Minimum stiffness of 35 PSI at 5% deflection when tested in accordance with ASTM D2412
<b>FLATTENING:</b>	Withstands 20% deflection with no evidence of buckling, cracking, or splitting.
<b>ENVIRONMENTAL RESISTANCE:</b>	Tested for environmental stress cracking, high temperature strength and low temperature flexibility with no evidence of failure.
<b>WARRANTY:</b>	3 Years
<b>FEATURES:</b>	Weather proof and UV resistant for outside installation year-round Easy to clean Light weight and easy to install Pre-slit for fast and clean installation Recyclable